


- NOTES:
1. ALL MATERIALS AND PROCESSES MUST CONFORM TO ROHS AS SPECIFIED IN 010-100594
 2. PACKING FILLS, BOXES AND LABELS MUST BE MANUFACTURED ACCORDING TO CHRISTIE DIGITAL SYSTEMS STANDARD # 010-101136-01: " PACKAGING LABELING AND MATERIAL GUIDELINE "
 3. REFER TO SUPPLIER QUALITY STANDARD 010-101164-01 FOR GENERAL QUALITY REQUIREMENTS AND PRACTICES, AND FOR CRITICAL FEATURE INSPECTION METHODS IF INDICATED WITH  ON THIS SPECIFICATION
 4. NOT ALL DIMENSIONS SHOWN. REFER TO CAD MATH DATA FOR DETAILS.
 5. CAD MATH DATA AND UNTOLERANCED DIMENSIONS ARE BASIC UNLESS OTHERWISE SPECIFIED

GENERAL NOTES:





MASS: 9.2 kg (20.3 lbs)

AMBIENT AIR TEMPERATURE: 40°C (104°F) MAX.
EXHAUST REQUIREMENTS: 70 cfm @ 40°C (104°F)



POWER REQUIREMENTS: SINGLE PHASE 100-240V, 12 AMP BREAKER
POWER CONSUMPTION: 110 W


ROOM HEAT LOAD: 375 btu/hr

REVISION HISTORY of: 020-100488-01			
REV	DESCRIPTION OF CHANGE	BY	DATE UPDATED
01	INITIAL RELEASE	PG	9/24/2009
02	ADD DIMENSIONS FOR M6 SLOTS IN LEVELLING FEET; NOTE OPTIONAL SET-UP KIT	PG	4/27/2010
03	UPDATE CG DIMENSION, ADD WALL MTG BRKT DETAILS (PG. 3)	PG	5/3/2010
04	UPDATE TORQUE SPEC ON REAR M6 BOLTS, ADD LENGTH OF SCREW ENGAGEMENT	PG	6/10/2010
05	UPDATED FOOT HOLE SPACING DIMENSION	BH	10/26/2010




ATTACHING SCREEN TO DISPLAY UNIT




MECH. REF # :	M036143	UNITS:	MILLIMETRES [INCHES]	CAD MAINTAINED DATA	CHRISTIE CHRISTIE DIGITAL SYSTEMS USA, INC. CHRISTIE DIGITAL SYSTEMS CANADA, INC.	
USED ON:	MICROTILES	UNLESS OTHERWISE SPECIFIED	INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994	CHANGES SHALL BE INCORPORATED ELECTRONICALLY		
MATERIAL:	NOT APPLICABLE	ALL DIMENSIONS SHOWN APPLY BEFORE	FLATINGS AND COATINGS	DRAWN BY	P. GROH	PART DESCRIPTION
DEBURRING:	NONE	TOLERANCES APPLY AS SHOWN BELOW		DRAWN DATE	9/24/2009	DWG LINE MICROTILES
FINISH:	NONE	DECIMAL PLACES	INCHES	PROPRIETARY NOT TO BE DISCLOSED OR REPRODUCED IN ANY MANNER WITHOUT THE EXPRESS WRITTEN PERMISSION OF CHRISTIE		SIZE
COATING:	NONE	.XXX .XX .X	± .005 ± .010 ± .020			D
I.D:	NONE	ANGULAR DIMENSIONS	XX° XX.X° SURFACE ROUGHNESS	THIRD ANGLE PROJECTION 		REVISION
SIMILAR TO:	NONE	± 0.5° ± 0.1° 63 MICRON	± 0.1 ± 0.3 1.6			020-100488-01 05
				SCALE	1:4	SHEET 1 OF 3
				MASS	0 LBS [0 KG]	



MICROTILE SHOWN WITH LEVELLING FEET




ATTACHING LEVELLING FEET WITH VERTICAL SCREWS





AIR FLOW





MINIMUM CLEARANCE ABOVE TOP ROW FOR PLACEMENT OF VERTICAL SCREWS




TWO MICROTILES WITH LEVELLING FEET




MICROTILE SHOWN WITH WALL MOUNTING BRACKET




ATTACHING WALL MOUNTING BRACKET WITH M6 BOLTS



FOUR MICROTILES WITH WALL MOUNTING BRACKETS



FOUR MICROTILES WITH WALL MOUNTING BRACKETS
REAR AXONOMETRIC VIEW



GENERAL NOTES:
POWER CABLE AND DATA CABLES CAN BE RUN THROUGH
THE BRACKET SIDE CUTOUTS