DP2K-20C

Compact DLP Cinema projector for screens up to 20m (65ft)



The Barco DP2K-20C is a compact digital cinema projector for theaters with screens up to 20m (65ft) wide, based on Texas Instruments' proven **0.98" DLP Cinema® chip.** It ensures a first-class movie experience with consistent picture brightness, rich contrast and vibrant colors. What's more, the DP2K-20C comes in a budget-friendly, compact form factor.

Low cost of ownership

Keeping operating cost low was a top priority when developing the DP2K-20C. All core components have therefore been designed for easy serviceability and extended product lifetime.

Easy maintenance

The DP2K-20C projector has an easy-to-use, fully **modular** architecture. This modularity significantly minimizes downtime, allows for a minimum spare parts stock and speeds up technicians' learning curves, which significantly reduces cost of ownership.

Also available with Barco Alchemy

The DP2K-20C is also available with the Barco Alchemy Integrated Cinema Media Processor.



Product specifications

DP2K-20C

| • | |
|-----------------------------|---|
| Digital MicroMirror Device™ | 3 x 0.98" DC2K dark metal devices |
| Native resolution | 2,048 x 1,080 pixels |
| Housing | Hermetically sealed DMDs and optical assembly |
| Lamp | 1.2kW - 4kW |
| Light output | 18,500 lumens |
| Screen size | Up to 20m / 65ft wide (screen gain 1.8 @ 14ftl) |
| Contrast ratio | 2,000:1 |
| Digital Video Inputs | 2 x DVI input both selectable as single and dual link |
| Prime lenses | 1.2 - 1.8 1.4 - 2.05 1.6 - 2.5 1.95 - 3.2 2.4 - 3.9 |
| Projector diagnostics | via PC touch panel via Communicator control software via SNMP agent |
| Power requirements | 220V |
| Dimensions | 558(H) x 694(W) x 1034(D) mm 22.0(H) x 27.3(W) x 40.7(D) inch NB.: min. 5 cm of air inlet spacing required at the bottom of projector |
| Weight | 102kg (225lbs) |
| Ambient temperature | 35°C / 95°F Max. |
| Options | ACS-2048 3D add-ons Touch panel Pedestal |



