

SILVER MINIMONITOR

IN-CEILING, IN-WALL, IN-ROOM



SILVER MINIMONITOR

IN-CEILING, IN-WALL, IN-ROOM

Triad's Silver MiniMonitor speakers are engineered to deliver striking music and cinema sound to high-end home applications with precision and power.

These speakers exhibit a traditional two-way design taken to the highest level, using acclaimed Scan-Speak Revelator® drivers—some of the finest performers in the business—and a premium, compact enclosure for high-output, high-sensitivity audio reproduction. The Silver MiniMonitor is professionally engineered for full-range audiophile sound in smaller venues, or it can be paired with a Triad Sub for larger power handling and output. Handcrafted in the US using the finest materials and components, Triad's fully engineered, sealed, and internally braced MDF enclosures deliver intricate acoustics and effortless playback, actualizing the artist's intent.

Triad's Silver MiniMonitors offer a professional-grade audiophile experience, achieving unobtrusive elegance while retaining the integrity of sound.

Triad's Silver MiniMonitor represents nothing less than extraordinary value, holding its own—and then some—against some of the world's most recognized high-end speakers.

FEATURES

- Compact, two-way design
- Fully engineered, premium MDF enclosure
- Acoustic suspension
- Custom paint matching available

IN-CEILING

- AcoustiPerf frameless metal grill
- 6" mounting depth
- 45 degree baffle angle directs sound at the listener

IN-WALL

- AcoustiPerf frameless metal grill
- 4" mounting depth

IN-ROOM

- Acoustic cloth grill
- Real wood veneer or custom finishes available (standard finish is black paint)

SILVER MINIMONITOR IN-CEILING, IN-WALL, IN-ROOM

SPECIFICATIONS

	MATERIALS	IN-CEILING/6	IN-WALL/4	IN-ROOM
Tweeter count		1	1	1
Tweeter size		1" (25 mm)	1" (25 mm)	1" (25 mm)
Tweeter type		Fabric dome	Fabric dome	Fabric dome
Woofer count		1	1	1
Woofer size		5 1/4" (14 cm)	5 1/4" (14 cm)	5 1/4" (14 cm)
Woofer type		Paper/fiber blend	Paper/fiber blend	Paper/fiber blend
	PERFORMANCE	IN-CEILING/6	IN-WALL/4	IN-ROOM
Recommended amplifier power		25 - 125W	25 - 125W	25 - 125W
Impedance		4 ohm	4 ohm	4 ohm
Sensitivity (dB @ 2.83V, 1 m)		87 dB	87 dB	87 dB
Frequency response (+/- 3 dB)		87 Hz - 20 kHz	87 Hz - 20 kHz	87 Hz - 20 kHz
	DIMENSIONS	IN-CEILING/6	IN-WALL/4	IN-ROOM
Cabinet specifications (L x W x D)		13 1/2 x 13 1/2 x 5 15/16" (34.3 x 34.3 x 15 cm)	11 15/16 x 8 3/16 x 3 15/16" (30.3 x 20.8 x 9.9 cm)	(no grill) 10 3/4 x 7 5/16 x 8 9/16" (no grill) (27.3 x 18.6 x 21.8 cm)
Hole cutout (L x W)		13 5/8 x 13 5/8" (34.6 x 34.6 cm)	12 1/16 x 8 5/16" (30.6 x 21.1 cm)	-
Frameless grill dimensions (L x W)		14 13/16 x 14 13/16" (37.6 x 37.6 cm)	13 1/4 x 9 1/12" (33.7 x 24.1 cm)	-
NCB size		G	B	-
Product weight (each)		15.5 lb (7 kg)	11 lb (4.9 kg)	15.75 lb (7.1 kg)
Shipping weight (each)		23 lb (10.4 kg)	14 lb (6.3 kg)	21 lb (9.5 kg)
	PRODUCT NUMBERS	IN-CEILING/6	IN-WALL/4	IN-ROOM
	Painted finish	-	45404-1000-2	25004-4000-1
	Veneer finish	-	-	25004-6000-1
	Right-side mounting	55504-1100-2	-	-
	Left-side mounting	55504-1200-2	-	-

Product page



triadspkrs.co/
silvminimon

DIMENSIONS

