



# Dolby® Storage Server and Integrated Media Block—ShowVault/IMB



The Dolby® ShowVault/IMB solution includes all hardware and software features of the digital cinema package (DCP) platform with numerous advanced features, such as dual 3G HD-SDI inputs, HDMI® 3D input with HDCP, 4K playback support, and scaling capabilities to 2K or 4K resolutions.

The Dolby ShowVault is a dedicated storage server capable of playing back 2D, 3D, and high-frame-rate (HFR) DCI-compliant DCPs, and it has been specifically developed to interface with the Dolby Integrated Media Block (IMB). The Dolby ShowVault loads digital content and dispenses files electronically to the IMB via an external PCI Express cable.

The Dolby IMB also supports deinterlacing of 1080i inputs and automatically converts incoming formats to avoid switching formats on the projector. All video inputs utilize a single audio output via RJ-45 for simple cabling to your audio processor of choice.

\* For DLP® Series 2 and select Sony® projectors only

## DOLBY IMB KEY FEATURES

- HDMI or HD-SDI (single or dual) inputs
- Scales supported video resolutions up to 4K
- Deinterlacing support (1080i)
- Automatic color-space conversions
- Support for accessibility products (Dolby Fidelio, Dolby CaptiView, and SMPTE ST 430-10 protocol)

\*Refer to user manual for a list of supported video resolutions.



## Dolby Storage Server and Integrated Media Block—ShowVault/IMB

### IMB

---

- HDMI input with HDCP support
- Dual 3G HD-SDI input
- Eight audio pairs (through two RJ-45 connectors)
- Eight general purpose outputs (RJ-45)
- Four general purpose inputs
- PCIe connection and gigabit Ethernet connection to Dolby ShowVault server
- Output resolution up to 4096 × 2160 in 2D and 2048 × 1080 in 3D
- HFR 3D 48 fps
- Dual-projector support
- LTC Output

### SHOWVAULT INTERFACE

---

- External PCI Express (for IMB communication)
- Gigabit Ethernet for media transfer
- Gigabit Ethernet for management control and subtitling
- RS-422 serial control port
- USB 2.0
- DVD-ROM\*
- CRU data port\*

### SHOWVAULT STORAGE

---

- Up to 6 TB of RAID 5 storage\*

### SHOWVAULT POWER

---

- Dual-redundant power supply
- 100–240 VAC; 50–60 Hz (300 W max)

### SHOWVAULT DIMENSIONS

---

- 4-U: 48 × 28 × 19 cm (19" × 11" × 7")

### FORMATS: ENCRYPTED/NONENCRYPTED

---

- JPEG 2000
- MPEG-2
- H.264

\*ShowVault 4-U

The English version of this document is the only legally binding version.  
Translated versions are not legally binding and are for convenience only.



Dolby Laboratories, Inc. 1275 Market Street, San Francisco, CA 94103-1410 USA T +1-415-558-0200 [dolby.com](http://dolby.com)

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories. All other trademarks remain the property of their respective owners. © 2016 Dolby Laboratories, Inc. All rights reserved.